

eDRAULIC – SPREADERS

SP 777 E2 / SP 555 E2 / SP 333 E2



	SP 777 E2	SP 555 E2	SP 333 E2
Spreading force	14,160 – 134,900 lbf. 63 – 600 kN	11,690 – 147,924 lbf. 52 – 658 kN	9,442 – 187,940 lbf. 42 – 836 kN
Spreading distance	32.0 in./813 mm	28.7 in./730 mm	23.6 in./600 mm
Squeezing force up to	27,400 lbf./122 kN	25,900 lbf./115 kN	32,500 lbf./144 kN
Pulling force up to	13,490 lbf./60 kN	13,039 lbf./58 kN	12,589 lbf./56 kN
Pulling distance	25.8 in./655 mm	22.4 in./569 mm	17.3 in./440 mm
Dimensions ¹⁾	42.5 × 12.2 × 11.2 in. 1,080 × 309 × 285 mm	39.4 × 10.4 × 11.0 in. 1,002 × 265 × 280 mm	35.6 × 10.0 × 11.2 in. 905 × 255 × 285 mm
Weight ²⁾	52.0 lbs./23.6 kg	44.1 lbs./20.0 kg	38.1 lbs./17.3 kg
Protection class	IP 54	IP 54	IP 54

¹⁾ l × w × h ²⁾ closed; w/o battery



SPREADING, SQUEEZING AND PULLING –
WHEN EVERY SECOND COUNTS

FLAT POINTS

Extra-flat points for narrow gap sizes

SHARK-TOOTH TIPS

Shark-tooth tips with aggressive grip for all kinds of operations

FITTING RAILS

Optional universal fitting rails for three additional lights

LOOP HANDLE

Flexible loop handle for turning the spreader in various positions

