

Bauer Junior II - E Compressor

The most compact highly mobile one of our diving compressor range. Due to its toughness and reliability the Junior has become a global classic. The Bauer Junior II offers an even more compact design and numerous improvements in details. The patented TRIPLEX® filter system guarantees purest breathing air according to DIN EN 12021 (formerly DIN 3188).



Invest in Bauer Quality

The Bauer Junior II is a product based on more than 50 years of experience and strict Bauer. Quality Management according to DIN EN ISO 9001. This is the uncompromising quality down to the last detail that has made us the global market leader for breathing air compressor units.

Easy Handling

- due to symbolic figures it is child´s play to operate the compressor
- comprehensive documentation facilitates maintenance work

Toughness

- durable, long-life compressor block
- new fan and pulley protection made of unbreakable
- uv-resistant special plastic, which improves cooling air flow for increased compressor efficiency
- filling device: stainless steel; filling hose: kevlar

Safe Handling

- moving parts such as v-belt, pulley and fan have optimal protection
- the GS-sign certifies the observation of all relevant safety regulations

TECHNICAL SPECIFICATIONS

Medium	Air
Intake Pressure	Atmospheric
Intake Temperature	+5°C to +45°C
Ambient Temperature	+5°C to +45°C
Setting of safety valve	225 or 330 bar
Filling pressure	200 or / and 300 bar
Capacity	100 l/min measured at bottle filling 0 to 200 bar Tolerance ± 5% at +20°C Ambient Temperature
Speed	2300 1/min
Number of Compression stages	3
Number of Cylinders	3



Bauer Junior II Compressor
Uncompromising quality